

DIGITAL TORQUE WRENCH



- Clockwise and counter-clockwise operation
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
 - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
 - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)
- Supplied with calibration certificate

SPECIFICATION

Code	Range	Accuracy	Resolution	Square driver (L)	Power supply	Length	Weight	
IST-W30A	6 ~ 30N.m	clockwise: $\pm 2\%$ counter-clockwise: $\pm 3\%$	0.01N.m	1/4"	2×AA batteries	390mm	830g	
IST-W135A	27 ~ 135N.m		0.1N.m	3/8"		415mm	950g	
IST-W200A	40 ~ 200N.m		0.1N.m	1/2"		530mm	1.4kg	
IST-W340A	68 ~ 340N.m		0.1N.m	1/2"		650mm	1.6kg	
IST-W500A	100 ~ 500N.m	clockwise: $\pm 2.5\%$ counter-clockwise: $\pm 3.5\%$	0.1N.m	3/4"		2×AA batteries	950mm	2.1kg
IST-W850A	170 ~ 850N.m		0.1N.m	3/4"			1220mm	2.55kg
IST-W1200A	240 ~ 1200N.m		1N.m	1"			1800mm	13kg
IST-W1500A	300 ~ 1500N.m		1N.m	1"			1800mm	13kg
IST-W2000A	400 ~ 2000N.m		1N.m	1"	1800mm		14kg	
					1800mm		14kg	

OPTIONAL ACCESSORY

Calibration cable	IST-W-CABLE
-------------------	-------------