

### SM4830 DATA SHEET

### 2.92mm Female to SSMA Female Adapter

#### **Electrical Specifications**

Frequency Range Maximum VSWR Maximum Insertion Loss DC to 25 GHz 1.35:1 0.316 dB

#### **Mechanical Specifications**

#### **Size**

Length

Weight

#### **Connector 1**

Type

Inner Conductor Material and Plating Body Material and Plating Dielectric Type

#### **Connector 2**

Type

Inner Conductor Material and Plating Body Material and Plating Dielectric Type

# **Environmental Specifications Temperature**

Operating Range

0.772 in [19.61 mm]

0.00794 lbs [3.6 g]

2.92mm Female Beryllium Copper, Gold Passivated Stainless Steel PTFE

SSMA Female Beryllium Copper, Gold Passivated Stainless Steel PTFE

-55 to +100 deg C

# **Compliance Certifications** (visit www.FairviewMicrowave.com for current document)

RoHS Compliant


Yes

#### Plotted and Other Data

Notes:

· Values at 25 °C, sea level

#### **Typical Performance Data**



ave Care

#### Features:

- Connector 1: 2.92mm Female
- Impedance 1: 50 Ohms
- Connector 2: SSMA Female
- Impedance 2: 50 Ohms
- · Adapter Design: Standard
- Body Style: Straight

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013

Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





2.92mm Female to SSMA Female Adapter from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: 2.92mm Female to SSMA Female Adapter SM4830


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order

URL: http://www.fairviewmicrowave.com/2.92mm-female-ssma-female-adapter-sm4830-p.aspx

to implem	nent improv	ements.	Fairview	/ Microwa	ave reserv	es the righ	nt to mak	ke such	changes	as requ	ired. Unles	s oth	nerwise
stated, al	l specificati	ons are	nominal.	Fairvie	w Microwa	ve does n	ot make	any rep	resentat	ion or v	warranty re	gard	ing the
suitability	of the par	t describ	ed hereir	n for any	particular particular	purpose,	and Fair	view M	crowave	does n	ot assume	any	liability
arising ou	t of the use	e of any	part or do	ocument	ation.								







FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES:  1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  3. DIMENSIONS ARE IN INCHES [mm].							
2.92mm Female to SSMA Female Adapter	DWG NO SM4830				CAGE CODE 3FKR5			
	CAD FILE 011415	SHEET	SCAL	E N/A	SIZE A	5568		