

Ultra DI[®] 50

Liquid Optical Particle Counter



Ultra DI particle counters are designed specifically for deionized (DI) water systems and will count and size contaminants as small as 0.05 μm .

The Ultra DI 50 particle counter's low zero count, large sample volume, and high counting efficiency provide unsurpassed performance.



BENEFITS

Rapid Analysis

- Quickly obtain meaningful statistical data with Ultra DI's large sample volume
- Save operator time with fast clean-up and the ability to move quickly from one sample point to another
- Speed up analysis time by using shorter sample intervals

Process Development

- Larger sample volumes and ultra-low zero counts detect smaller excursions with more relevant statistical data
- Respond immediately to contamination with real-time measurement of particles
- Facility Net software provides more sophisticated process control with:
 - alphanumeric paging
 - sensor status
 - tabular and SPC charts
 - time plots
 - historical event log records
- Set tighter process control limits with low sample-to-sample variation
- Detect process variations more quickly with improved sensitivity: 0.05 μm

Easy to Use

- Utilize existing network with Ethernet communication
- Connect directly to PLC and SCADA systems with 4-20 mA
- Compatible with ozonated water
- Stainless steel housing and dual HEPA filtration allow use in dirty environments

APPLICATIONS

- Quantifying particle concentration in state-of-the-art ultra pure water (UPW) systems
- Filter efficiency measurements
- Trending analysis at lower particle concentrations
- Detecting bacterial growth in UPW systems
- Episodic event tracking and alarming
- Continuous system monitoring
- Manufacturing process control

Without measurement there is no control.

Ultra DI[®] 50

Liquid Optical Particle Counter

specifications

Size range	0.05 – 0.20 µm
Channels	4
Channel sizes	0.05, 0.10, 0.15, 0.20 µm
Flow rate (ml/min)	1,000 ml/min ± 10%
Counting efficiency	100% sample volume
Sample volume	≥ 3.75 ml/min
Maximum concentration ¹	10,000 counts/ml
Sample temperature ²	59 – 122 °F (15 – 50 °C)
Maximum pressure	100 psi
Zero count	≤ 50 counts/L
Exterior surface	Stainless steel
Wetted surface materials	Teflon [®] , Kel-F [®] , fused silica, sapphire, Viton [®] , 96% Alumina Ceramic, and Simriz [®]
Dimensions (d, w, h)	17 x 17 x 10.5 in (43 x 43 x 27 cm)
Weight	45 lb (20.4 kg)
Power	100 – 240 VAC
Communications	Ethernet, 4-20 mA (3 outputs: 2 particle channels, 1 instrument status), RS-232 (set up and diagnostics only, no data)
Status indicator	Laser, power, and activity: one (1) tri-color LED
Calibration	Materials used are traceable to National Institute of Standards and Technology (NIST) and/or Japanese Industrial Standards (JIS)
Environment	Temperature: 59 – 86 °F (15 – 30 °C) Humidity, Non-Condensing

¹Greater than 90% accuracy (less than 10% coincidence loss) at the maximum recommended concentration.

²For temperatures greater than 50°C, use of a chiller is recommended.

Ultra DI[®] is a registered trademark of Particle Measuring Systems, Inc.

All other trademarks are the property of their respective owners.

Particle Measuring Systems, Inc. reserves the right to change specifications without notice.



Particle Measuring Systems Headquarters
5475 Airport Blvd., Boulder, CO 80301, USA
Tel: +1 303 443-7100 +1 800 238-1801

FAX: +1 303 449-6870

Instrument Service & Support: +1 800-557-6363

Customer Response Center: +1 877-475-3317

PMS EMEA
Tel: +44 1684 581 000
Email: PMSEMEA@pmeasuring.com

Particle Measuring Systems France
Tel: +33 160 10 32 96
Email: PMSFrance@pmeasuring.com

Particle Measuring Systems Germany
Tel: +49 2222 9299 522
Email: PMSGermany@pmeasuring.com

Particle Measuring Systems Italia
Tel: +39 06 9053 0130
Email: PMSIRL@pmeasuring.com

Particle Measuring Systems Nordic
Tel: +45 707 028 55
Email: PMSNordic@pmeasuring.com

Particle Measuring Systems China
Tel: +86 21 6113 3600
Email: pmschina@pmeasuring.com

Particle Measuring Systems Japan
Tel: +81 3 5298 8175
Email: PMSJapan@pmeasuring.com

Particle Measuring Systems Singapore
Tel: +65 6496 0330
Email: PMSSingapore@pmeasuring.com

AUTHORIZED REPRESENTATIVE

Particle Measuring Systems Brazil
Tel: +55 11 5188 8166
Email: PMSBrazil@pmeasuring.com

Particle Measuring Systems Mexico
Tel: +52 55 2271 5106
Email: PMSMexico@pmeasuring.com

Particle Measuring Systems Puerto Rico
Tel: +1 787 718 9096
Email: PMSPuertoRico@pmeasuring.com