



RG316 Flexible Coax Cable FEP Jacket

Electrical Specifications

Description	Min	Тур	Max	Units		
Frequency Range	DC		3	GHz		
Impedance		50		Ohms		
Velocity of Propagation		70		%		
Operating Voltage (AC)			1,200	Vrms		
Nominal Capacitance		32		pF/ft		
		[104.99]				

Mechanical Specifications

Diameter Weight 0.098 in [2.49 mm] 0.011 lbs/ft [0.02 Kg/m]

Min. Bend Radius (Installation)

0.512 in [13 mm]

Construction Specifications

Description	Material and Plating	Diameter						
Inner Conductor	Copper, Silver, 7 Strands	0.06 in [1.52 mm]						
Conductor Type	Solid							
Dielectric	PTFE	0.06 in [1.52 mm]						
First Shield	Silver Plated Copper Braid	Silver Plated Copper Braid						
Jacket	FEP	0.098 in [2.49 mm]						

Environmental Specifications

Temperature

Operating Range -55 to +125 deg C

Compliance Certifications (visit www.FairviewMicrowave.com for current

document)

RoHS Compliant Yes

Plotted and Other Data

Notes:



Configuration:

- Flexible Cable
- 1 Shield(s)

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013 Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





RG316 Flexible Coax Cable FEP Jacket from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order

Click the following link to obtain additional part information: RG316 Flexible Coax Cable FEP Jacket RG316

URL: http://www.fairviewmicrowave.com/rg316-flexible-coax-cable-fep-jacket-rg316-p.aspx

stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.	to implem	ent improv	ements.	Fairview	/ Microw	ave reserve	es the righ	nt to ma	ke such	ı chan	ges as	requ	ired. U	nless c	therwise
	stated, all	specification	ons are	nominal.	Fairvie	w Microwa	ve does n	ot make	any re	eprese	entatio	n or v	varranty	rega	ding the
arising out of the use of any part or documentation.	suitability	of the part	t describ	ed hereir	n for any	particular	purpose,	and Fa	irview N	4icrov	vave d	oes n	ot assu	me an	y liability
	arising ou	t of the use	e of any	part or do	ocument	ation.									





FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
RG316 Flexible Coax Cable FEP Jacket	DWG NO RG316			CAGE CODE 3FKR5		
	CAD FILE 120315	SHEET	SCALI	E N/A	SIZE A	5568