

**GB 18 LTX BL Q I (603828890) Cordless Tappers**  
**18V Li-ion; Cardboard box**

Order no. 603828890  
EAN 4007430333582



Product may differ from Image



- High-grade cordless drill/screwdriver with unique, patented thread-tapping function
- Quick and interruption-free cutting and cleaning of threads thanks to automatic change of direction of rotation
- Two quick-change tapping chuck for inserting taps with square and cylindrical shanks
- Metabo "Quick" System: quick change of bit retainer and bits for flexible working
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- Handy belt hook and bit holder can be fixed either on the right or left side
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

## Technical data

### Characteristics

|                                 |                             |
|---------------------------------|-----------------------------|
| Type of battery pack            | Li-ion                      |
| Battery voltage                 | 18 V                        |
| Maximum torque - soft           | 60 Nm / 531 in-lbs          |
| Maximum torque, hard            | 120 Nm / 1062 in-lbs        |
| Adjustable torque               | 1 - 20 Nm // 9 - 177 in-lbs |
| Thread diameter                 | M4 - M12                    |
| Drill Ø steel                   | 13 mm / 1/2 "               |
| Drill-Ø soft wood               | 65 mm / 2 1/2 "             |
| No-load speed                   | 0 - 500 / 0 - 1850 rpm      |
| Chuck capacity                  | 1.5 - 13 mm // 1/32 - 1/2 " |
| Weight (including battery pack) | 5.5 lbs / 2.5 kg            |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Drilling in metal            | 3.2 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 78 dB(A) |
| Sound power level (LwA)      | 89 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Quick-change tapping chuck M4-M6  
 Belt hook and bit case  
 MetaLoc case insert  
 MetaLoc case insert  
 without battery pack, without charger  
 Quick-change tapping chuck M8-M12  
 Side handle