

## TKHS 315 M - 3,1 WNB (0103153100) Table Saw (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 0103153100 EAN 4003665403403



Product may differ from Image





- Restart protection: prevents unintentional start-up after power supply interruption
- Precise, powerful table saw in professional configuration quick to adapt for every application
- Ideal for sawing squared timber, boards, panels and wood-like materials in the workshop and at construction sites
- Quiet induction motor with motor brake and overload protection maintenance-free and robust.
- Mitre fence with linear stop, can also be used a sliding table
- Sturdy parallel guide/ripping fence with quick fastening
- Freely height-adjustable saw blade
- Comfortable setting of the saw blade inclination from the front
- Sturdy, powder-coated sheet steel design and galvanised table-top
- Foldable table length extension
- Frame and motor pre-mounted

www.metabo.com 1/2



Technical data	
Characteristics	
Dimensions	1700 x 700 x 1000 mm / 5.6 x 2.3 x 3.3 ft
Max. support surface	800 x 600 mm / 31 1/2 x 23 5/8 "
Working height	850 mm / 33 1/2 "
Cutting height	0 - 85 mm // 0 - 3 5/16 "
Maximum cutting height 90/45°	85 / 53 mm // 3 5/16 / 2 1/16 "
Maximum cutting width at parallel guide/rip fence	340 mm / 13 3/8 "
Maximum material width at mitre fence	250 mm / 9 13/16 "
No-load speed	2990 rpm
Cutting speed	50 m/s / 164 ft/s
Saw blade	315 x 30 mm / 12 3/8 x 1.181 "
Saw blade swivel range	0 - 45 °
Mains voltage	220 - 240 V
Rated input power	3100 W
Weight	75 kg / 165 lbs kg
Noise emission	
Sound pressure level	97 dB(A)
Sound power level (LwA)	106 dB(A)
Uncertainty of measurement K	4 dB(A)

## Scope of delivery

Carbide saw blade with alternately bevel-ground tips (24 teeth)

Mitre Fence

Table extension (600 x 800 mm)

Chip and Dust Extraction Unit

Push stick

Wheel set incl. handles

Parallel Guide / Rip Fence

www.metabo.com 2/2